

TEST PARAMETER



CHARACTERISTICS	TEST METHOD	RESULT
Dimension	EN 427	118x590mm
Thickness-Overall	EN 428	5.0mm
Thickness-Wear Layer	EN 429	0.5mm
Total Weight	EN 430	10.00kg/m ³
Caster Wheer Chair	EN 425	Pass
Abrasion Resistance	EN 660-2	T Grade
Indentation Residual	EN 433	Pass
Colour Fastness	EN ISO 105-BO2	≥6
Impact Sound Reduction	EN ISO 10140-3	19dB
Fire Rating	EN13501-1	B _f -s1
Effects of Stain	EN 423	Pass
Residual Indentation after Stability	EN 434	Shrinkage ≤0.08% Curlings≤2.0mm
Peeling Strength of Layers	EN 431	Pass
Flexibility - 10mm Mandrel	EN 435	No Damage
Resistance to Chemicals	EN 423	Class 0
Toxic	EN 71Part3	Pass
Slip Resistance	DIN 13893	R10
Performance Classification	EN 685	23/34/43
GB/T 4085 GB 86t24 B1		Pass
CNS 8907		Pass

Suitable for use with underfloor heating up to 27°C

Wear guarantee:
Lifetime Residential
15 Years Commercial

